

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claims 1-6 (canceled).

Claim 7 (new): A signal output circuit comprising:

an output transistor of an NPN type bipolar transistor arranged to output an output signal;

a ground side output control transistor that turns ON and OFF according to an input signal so that turning ON drops the potential of a base of the output transistor to turn OFF the output transistor, and turning OFF raises the potential of the base of the output transistor to turn ON the output transistor;

a base current supply resistive element arranged to supply current from an input power supply to the base of the output transistor;

a power supply side output control transistor located between the base current supply resistive element and the base of the output transistor and arranged to turn ON and OFF in opposite ways as the ground side output control transistor according to the input signal;

a ground side current bypass transistor, that turns ON and OFF in the same way as the ground side output control transistor according to the input signal so that turning ON allows current of the base current supply resistive element to flow and turning OFF stops the current of the base current supply resistive element from flowing; and

a current limitation resistive element located between the ground side current bypass transistor and the base current supply resistive element.

Claim 8 (new): The signal output circuit according to Claim 7, further comprising an inversion circuit to which the voltage between the ground side current bypass transistor and the current limitation resistive element is input so as to invert the input voltage to control the power supply side output control transistor.

Claim 9 (new): The signal output circuit according to Claim 8, further comprising a second current limitation resistive element connected to the output of said inversion circuit.

Claim 10 (new): The signal output circuit according to Claim 7, wherein the ground side output control transistor, the power supply side output control transistor and the ground side current bypass transistor are MOS transistors.

Claim 11 (new): The signal output circuit according to Claim 7, wherein the base current supply resistive element, the current limitation resistive element and the second current limitation resistive element are resistors.

Claim 12 (new): A power supply voltage monitoring device comprising the signal output circuit according to Claim 7, further comprising:

resistive elements connected in series and arranged to divide the power supply voltage;

a reference voltage generation circuit arranged to generate the reference voltage; and

a comparator arranged to compare the voltage at a mid-point of said resistive elements connected in series and the reference voltage generated by said reference voltage generation circuit so as to use the comparison output as an input signal of the signal output circuit, wherein the output signal of the signal output circuit is output as a power supply voltage monitoring signal.

Claim 13 (new): A power supply voltage monitoring device comprising the signal output circuit according to Claim 8, further comprising:

resistive elements connected in series and arranged to divide the power supply voltage;

a reference voltage generation circuit arranged to generate the reference voltage; and

a comparator arranged to compare the voltage at a mid-point of said resistive elements connected in series and the reference voltage generated by said reference voltage generation circuit so as to use the comparison output as an input signal of the signal output circuit, wherein the output signal of the signal output circuit is output as a power supply voltage monitoring signal.

Claim 14 (new): A power supply voltage monitoring device comprising the signal output circuit according to Claim 8, further comprising:

resistive elements connected in series and arranged to divide the power supply voltage;

a reference voltage generation circuit arranged to generate the reference voltage; and

a comparator arranged to compare the voltage at a mid-point of said resistive elements connected in series and the reference voltage generated by said reference voltage generation circuit so as to use the comparison output as an input signal of the signal output circuit, wherein the output signal of the signal output circuit is output as a power supply voltage monitoring signal.